

Retro-fitting FTICKS to FreeRADIUS

IN PROGRESS

For a [brief explanation of FTICKS](#) and why they're useful.

What we're trying to achieve is for an RFO to send us logs of just the successful authentications happening between your registered organisations (i.e. not the ones proxies to and from the Jisc NRPS).

To do this there are a few stages.

1. Modify the client stanzas to include an 'operator=<realm>' line which will set the internal 'operator' variable to identify the organisation from which the request originates. e.g:

```
client somesite {
    secret = something
    ipaddr = 192.168.0.1
    operator = "somesite.nhs.uk"
}
```

2. Modify the client stanzas to identify all the Jisc NRPS as 'operator=NRPS', as above. e.g:

```
client roaming0 {
    secret = something
    ipaddr = 192.168.0.1
    operator = "NRPS"
}
```

3. Add a log section for FTICKS which sends the logs to syslog.

4. Modify the post-auth stanza to use the above log section only where the source and destination aren't 'NRPS'. e.g:

```
        # Only send F-TICKS to Jisc when proxying between sites.
        if ( "%{home_server:operator}" != "NRPS" && "%{client:operator}" !=
"NRPS") {
            f_ticks
        }
```

5. Configure a [syslog server](#) to proxy to the FTICKS syslog to the Jisc syslog server.

Last update: 2024/03/19 08:17 public:retro-fitting_fticks_logging_to_freeradius https://wiki.govroam.uk/doku.php?id=public:retro-fitting_fticks_logging_to_freeradius&rev=1710836239

From: <https://wiki.govroam.uk/> - **Govroam**

Permanent link: https://wiki.govroam.uk/doku.php?id=public:retro-fitting_fticks_logging_to_freeradius&rev=1710836239

Last update: **2024/03/19 08:17**

