

```
# Some basic logging
LogLevel 3
LogDestination          x-syslog:///LOG_DAEMON

# Prevents RADIUS servers from causing a loop by sending requests back
again.
LoopPrevention          On
# FTICKS is a standardised way of logging authentication attempts.
FTicksSyslogFacility LOG_LOCAL0
FTicksReporting Full
FTicksMAC VendorKeyHashed
FTicksKey arandomsalt

# Upstream RADIUS proxy
server nrps1 {
    host 10.10.10.31
    type udp
    secret XXXX
    statusServer on   #This checks that status of the adjacent servers.
}

# Local IdP which will do the authentication (Omit for Visited Only)
server localidp1 {
    host 10.10.10.21
    type udp
    secret XXXX
    statusServer on
}

# RADIUS requests will also be received from the national proxies.
client nrps1 {
    host 10.10.10.31
    type udp
    secret XXXX
}
client localidp1 {
    host 10.10.10.21
    type udp
    secret XXXX
}

# Wireless system
client nas {
    host 10.10.10.10
    type udp
    secret XXXX
    fticksVISCOUNTRY GB
    fticksVISINST 1localnet      # Adding information to the logs
```

```
about this client.  
}  
  
#Known local realm (Omit for Visited Only)  
realm localnet {  
    server localidp1  
    AccountingResponse On  
}  
  
#Default destination for unknown realms  
realm * {  
    server nrps1  
    AccountingResponse On  
}
```

From:
<https://wiki.govroam.uk/> - Govroam

Permanent link:
https://wiki.govroam.uk/doku.php?id=siteadmin:basic_orps_radsecproxy_configuration&rev=1615303443

Last update: **2021/03/09 15:24**

