2025/11/01 14:30 1/1 Adding Operator-Name

## **Adding Operator-Name**

Cisco ISE doesn't insert O-N into the Request by default. O-N helps Home sites identify where their users' authentications are coming from. Combined with Chargeable User Identity, Home and Visited sites can provide and follow an audit trail back to a user without the Visited site knowing the users' details.

## Adding the Operator-Name attribute

- Go to Policy → Policy Elements → Dictionaries.
- Open up the **System** dropdown.
- Open up the **Radius** dropdown.
- Click on IETF.
- Click on unknown-126 and enter
  - Attribute Name as 'Operator-Name'
  - Data Type as STRING
  - Direction as IN
- Click Save

## **Modify the Request packet**

- Go to Administration → Network Resources → RADIUS Server Sequences.
- Click on which-ever server sequence relates to the Jisc NRPS.
- Click on Advanced Attribute Settings
- Enable Modify Attribute in the request
- Choose Add Govroam:Operator-Name 1realm (where realm is your primary realm e.g. 1holby.local)
- Click Save

Note: Due to a bug in ISE I was unable to fully test this. Feedback would be appreciated.

From:

https://wiki.govroam.uk/ - Govroam

Permanent link:

https://wiki.govroam.uk/doku.php?id=siteadmin:operator-name\_for\_cisco\_ise&rev=166254257

Last update: 2022/09/07 09:22

