2025/08/28 07:39 1/3 General Troubleshooting

General Troubleshooting

Common Problems

The govroam monitoring system should be sending ICMP and RADIUS requests to your servers quite frequently (several times every five minutes). So you should be able to see these in your firewall logs or using Wireshark on your server. If you can't then check your firewall settings to allow ICMP echo/response and UDP port 1812 (incoming for Home sites, outgoing for Visited).

A log message similar to: "message authenticator attribute that is not valid" means, most likely, that the shared secret with the sending system is incorrect.

Rejected authentication requests

This is one diagnosed by Hans Litteck from the University of London.

He'd noticed that attempts to authenticate a test user were failing and worked with Camden Council to figure it out. Thanks to all involved.

The exective summary is that Microsoft NPS was configured to reject any request that wasn't formatted like:

```
Called-Station-ID =~ :govroam$
```

i.e. the Called-Station-ID should have a suffix of ':govroam' after the address of the device.

To quote Hans:

I'm aware RFC 3580 states the Called-Station-ID SHOULD append the SSID. However,

- 1. Not everything does; ArubaOS below 6.4 doesn't allow you to add this to the RADIUS client configuration.
- 2. The default pre-proxy attribute filter in FreeRADIUS, if turned on, will remove Called-Station-ID from a proxy request.

So the policy condition is a bit strict for a 'federated' environment.

I've update our FreeRADIUS configuration to add the missing SSID if not supplied by the NAS client and I can now authenticate via Camden's RADIUS server.

Further to this Hans has looked into the attribute filters and determined that NPS should be configured not to filter out the following from a proxied request:

NAS-IP-Address NAS-Identifier NAS-Port NAS-Port-Type Service-Type

My interpretation is it that a RADIUS server will always see those if the request comes direct from a NAS client (AP, wireless controller, edge switch, ...) but not necessarily for a proxy request especially of the visited site uses filtering.

What isn't know at the moment is if this standard NPS policy or a configuration being placed on NPS by administrators.

A general note about attributes and filtering

The Govroam tech spec talks about attributes and what should be in the various packets and what shouldn't. The key things to note, relevant to the above, are in section 2.4.1.13:

The following RADIUS attributes MUST be forwarded unaltered by participants' ORPSs if present in RADIUS Access-Request, Access-Challenge, Access-Accept or Access-Reject messages.

- 13.1. User-Name
- 13.2. Reply-Message
- 13.3. State
- 13.4. Class
- 13.5. Message-Authenticator
- 13.6. Proxy-State
- 13.7. EAP-Message
- 13.8. MS-MPPE-Send-Key
- 13.9. MS-MPPE-Recv-Key
- 13.10. Calling-Station-Id
- 13.11. Operator-Name
- 13.12. Chargeable-User-Identity

Participants' ORPSs MUST log all RADIUS authentication requests exchanged

which is fine but if RADIUS servers are expecting OTHER attributes, such as NAS-*, and rejecting if they're not there then it'll cause a problem, as seen above. The discussion section 2.4.3 says:

The inclusion of spurious RADIUS attributes in packets exchanged between organisations can have unexpected effects and result in problems. It is therefore best practice to filter out unnecessary attributes. It is however essential that the key attributes detailed in this specification are not filtered and must be retained in forwarded packets.

So the solution to the problem of failed authentications is to NOT filter out certain attributes and the

https://wiki.govroam.uk/ Printed on 2025/08/28 07:39

2025/08/28 07:39 3/3 General Troubleshooting

spec says that they ought to be. Which is correct? The best advice is to filter out these attributes when proxing outwards but if there are any authentication issues with remote sites that you're struggling to fix then consider removing the filter to see what happens.

At the same time ensure that your RADIUS is NOT configured to expect these extra attributes. It WILL be possible to run a service with just the key attributes mentioned in the spec.

From:

https://wiki.govroam.uk/ - Govroam

Permanent link:

https://wiki.govroam.uk/doku.php?id=siteadmin:radius_troubleshooting&rev=1566999146

Last update: 2019/08/28 13:32

