

Advanced ORPS RADSECProxy Configuration

This should be representative of the configuration used in production. It contains the appropriate logging and filtering.

```
# Some basic logging
LogLevel 3
LogDestination          x-syslog:///LOG_DAEMON

# Prevents RADIUS servers from causing a loop by sending requests back
again.
LoopPrevention          On
# FTICKS is a standardised way of logging authentication attempts.
FTicksSyslogFacility LOG_LOCAL0
FTicksReporting Full
FTicksMAC VendorKeyHashed
FTicksKey arandomsalt

rewrite OutboundFilter {
    # Operator-Name
    RemoveAttribute 126
    AddAttribute 126:'!home.site

    WhitelistMode on
    # User-Name
    WhitelistAttribute 1
    # EAP-Message
    WhitelistAttribute 79
    # Message-Authenticator
    WhitelistAttribute 80
    # State
    WhitelistAttribute 24
    # Proxy-State
    WhitelistAttribute 33
    # Operator-Name
    WhitelistAttribute 126
    # Class
    WhitelistAttribute 25
    # Calling-Station-Id
    WhitelistAttribute 31
    # Called-Station-Id
    WhitelistAttribute 30
    # Chargeable-User-Identity
    WhitelistAttribute 89
}

# Upstream RADIUS proxy
server roaming@govroam.uk {
```

```
host 212.219.190.139
type udp
secret XXXX
RewriteOut OutboundFilter
statusServer minimal #This checks that status of the adjacent
servers.
}

# Upstream RADIUS proxy (Omit for Visited Only)
server roaming1.govroam.uk {
host 212.219.209.43
type udp
secret XXXX
RewriteOut OutboundFilter
statusServer minimal #This checks that status of the adjacent
servers.
}

# Upstream RADIUS proxy (Omit for Visited Only)
server roaming2.govroam.uk {
host 212.219.247.59
type udp
secret XXXX
RewriteOut OutboundFilter
statusServer minimal #This checks that status of the adjacent
servers.
}

# Upstream RADIUS proxy (Omit for Visited Only)
server roaming3.govroam.uk {
host 195.194.21.203
type udp
secret XXXX
RewriteOut OutboundFilter
statusServer minimal #This checks that status of the adjacent
servers.
}

# Local IdP which will do the authentication (Omit for Visited Only)
server localidp1 {
host 10.10.10.21
type udp
secret XXXX
statusServer auto
}

# RADIUS requests will also be received from the national proxies. (Omit for
Visited Only)
```

```
client roaming0.govroam.uk {
    host 212.219.190.139
    type udp
    secret XXXX
}
client roaming1.govroam.uk {
    host 212.219.209.43
    type udp
    secret XXXX
}
client roaming2.govroam.uk {
    host 212.219.247.59
    type udp
    secret XXXX
}
client roaming3.govroam.uk {
    host 195.194.21.203
    type udp
    secret XXXX
}

# Wireless system
client nas {
    host 10.10.10.10
    type udp
    secret XXXX
    fticksVISICOUNTRY GB
    fticksVISINST lhome.site          # Adding information to the logs
about this client.
}

#Known local realm (Omit for Visited Only)
realm localnet {
    server localidp1
}

### Catch a load of common misconfigurations
realm /^$/ {
    replymessage "Misconfigured client: empty realm!"
}

realm
/@@((myabc|gmail|googlemail|hotmail|live|outlook|yahoo|unimail).com|(.*\.)?3g
ppnetworks?.org|yahoo.cn) {
    replymessage "Misconfigured client: govroam realm not permitted"
}

realm /@@(.*\.(ax\.uk|ax\.edu|sc\.uk|ac\.edu|ac\.u|local)|ac\.uk)$ {
    replymessage "Misconfigured client: govroam realm invalid (typo?)"
}
```

```
realm /@\. {
    replymessage "Misconfigured client: govroam realm invalid (leading '.')"
}

realm /@[^\.]+" {
    replymessage "Misconfigured client: govroam realm invalid (incomplete)"
}

### Check it's a syntactically correct realm and proxy if ok
realm /@[0-9a-zA-Z\.]+"\.[0-9a-zA-Z\.]+" {
    server roaming0.govroam.uk
    server roaming1.govroam.uk
    server roaming2.govroam.uk
    server roaming3.govroam.uk
}

### Otherwise reject it
realm * {
    replymessage "Misconfigured client: govroam realm invalid (syntax error)"
}
```

From: <https://wiki.govroam.uk/dokuwiki/> - Govroam

Permanent link: https://wiki.govroam.uk/dokuwiki/doku.php?id=siteadmin:advanced_orps_radsecproxy_configuration&rev=1615303394

Last update: 2021/03/09 15:23

