```
# Some basic logging
LogLevel 3
LogDestination         x-syslog:///LOG_DAEMON

# Prevents RADIUS servers from causing a loop by sending requests back
again.
LoopPrevention         On
# FTICKS is a standardised way of logging authentication attempts.
FTicksSyslogFacility LOG_LOCAL0
FTicksReporting Full
FTicksMAC VendorKeyHashed
FTicksKey arandomsalt


# Upstream RADIUS proxy
server  nrps0 {
        host 10.10.10.31
        type udp
        secret XXXX
        statusServer on   #This checks that status of the adjacent servers.
}


# Local IdP which will do the authentication (Omit for Visited Only)
server  localidp0 {
        host 10.10.10.21
        type udp
        secret XXXX
        statusServer on
}


# RADIUS requests will also be received from the national proxies. (Omit for
Visited Only)
client  nrps0 {
        host roaming0.govroam.uk
        type udp
        secret XXXX
}
client  localidp0 {
        host 10.10.10.21
        type udp
        secret XXXX
}

# Wireless system
client  nas {
        host 10.10.10.10
        type udp
        secret XXXX
        fticksVISCOUNTRY GB
```

```
        fticksVISINST 1localnet        # Adding information to the logs
about this client.
}

#Known local realm (Omit for Visited Only)
realm localnet {
        server localidp0
        AccountingResponse On
}

#Default destination for unknown realms
realm * {
        server nrps0
        AccountingResponse On
}
```

From:
https://wiki.govroam.uk/dokuwiki/ - **Govroam**

Permanent link:
https://wiki.govroam.uk/dokuwiki/doku.php?id=siteadmin:basic_orps_radsecproxy_configuration&rev=1615303574

Last update: **2021/03/09 15:26**