

```

route_realms {
    ## make sure our domains are sent to the AD proxy's
    if (&Stripped-User-Domain =~ /^bath\.ac\.uk$/) {
        ## send requests for bath.ac.uk to the ad servers
        update {
            control:Load-Balance-Key := &Calling-Station-ID
            control:Proxy-To-Realm := 'PROXY-AD'
            request:Realm := 'PROXY-AD'
        }
    }
    } else {
        if (&request:NAS-Identifier =~ /^mwr-test-eduroam$/) {
            ## send it to janets eduroam servers
            update {
                control:Load-Balance-Key := &Calling-
Station-ID
                control:Proxy-To-Realm := 'PROXY-JANET-
EDUROAM'
                request:Realm := 'PROXY-JANET-EDUROAM'

                ## RFC5580 says that we should be nice and
send a Namespace ID (1 = REALM) and an operator name
                ## so people know where the request came
from and who to should at if there are problems
                ## we could carry this between servers if we
ever needed to have multiple realms
                #request:Operator-Name := "1bristol.ac.uk"
                ... just kidding :)
                request:Operator-Name := "1bath.ac.uk"
            }
        }

        if (&request:NAS-Identifier =~ /^eduroam$/) {
            ## send it to janets eduroam servers
            update {
                control:Load-Balance-Key := &Calling-
Station-ID
                control:Proxy-To-Realm := 'PROXY-JANET-
EDUROAM'
                request:Realm := 'PROXY-JANET-EDUROAM'

                ## RFC5580 says that we should be nice and
send a Namespace ID (1 = REALM) and an operator name
                ## so people know where the request came
from and who to should at if there are problems
                ## we could carry this between servers if we
ever needed to have multiple realms
                #request:Operator-Name := "1bristol.ac.uk"
                ... just kidding :)
                request:Operator-Name := "1bath.ac.uk"
            }
        }
    }
}

```

```
    }

    if (&request:Called-Station-Id =~ /:eduroam$/) {
        ## send it to janets eduroam servers
        update {
            control:Load-Balance-Key := &Calling-
Station-ID
            control:Proxy-To-Realm := 'PROXY-JANET-
EDUROAM'
            request:Realm := 'PROXY-JANET-EDUROAM'

            ## RFC5580 says that we should be nice and
send a Namespace ID (1 = REALM) and an operator name
            ## so people know where the request came
from and who to should at if there are problems
            ## we could carry this between servers if we
ever needed to have multiple realms
            #request:Operator-Name := "lbristol.ac.uk"
... just kidding :)
            request:Operator-Name := "lbath.ac.uk"
        }
    }

    if (&request:NAS-Identifier =~ /^govroam$/) {
        ## send it to janets govroam servers
        update {
            control:Load-Balance-Key := &Calling-
Station-ID
            control:Proxy-To-Realm := 'PROXY-JANET-
GOVROAM'
            request:Realm := 'PROXY-JANET-GOVROAM'

            ## RFC5580 says that we should be nice and
send a Namespace ID (1 = REALM) and an operator name
            ## so people know where the request came
from and who to should at if there are problems
            ## we could carry this between servers if we
ever needed to have multiple realms
            #request:Operator-Name := "lbristol.ac.uk"
... just kidding :)
            request:Operator-Name := "lbath.ac.uk"
        }
    }
}
```

Many thanks to Matt Richards from Bath University for this.

From:
<https://wiki.govroam.uk/dokuwiki/> - **Govroam**

Permanent link:
https://wiki.govroam.uk/dokuwiki/doku.php?id=siteadmin:freeradius_useful_configuration&rev=1575543294

Last update: **2019/12/05 10:54**

