## **FTICKS for NPS**

NOTE: This is untested.

## Installation

Download NXLog Community Edition from here:

https://nxlog.co/products/nxlog-community-edition/download

and install it. Make of note of where the nxlog.conf file is.

## Configuration

Edit the *nxlog.conf* file and add the following to the end:

```
<Output syslog_tls>
    Module
                om ssl
    Host
                212.219.243.132
    Port
                6514
    CAFile
                c:/Program Files (x86)/nxlog/data/cacert.pem
                c:/Program Files (x86)/nxlog/data/clientreq.pem
    CertFile
    CertKeyFile c:/Program Files (x86)/nxlog/data/clientkey.pem
    AllowUntrusted 1
    OutputType Syslog TLS
                to syslog ietf();
    Exec
</Output>
<Output syslog_tcp>
    Module
                om tcp
    Host
                212.219.243.132
    Port
                601
    OutputType Syslog TLS
                to_syslog_ietf();
    Exec
</Output>
<Input eventlog>
    Module im_msvistalog
    <QueryXML>
      <QueryList>
        <Query Id="0" Path="System">
          <Select Path="System">*[System[Provider[@Name='NPS']]]</Select>
          <Select Path="Security">*[System[Provider[@Name='Microsoft-
Windows-Security-Auditing'] and Task = 12552]]</Select>
        </Query>
      </QueryList>
```

</QueryXML> </Input> <Route 1> Path eventlog => syslog\_tcp </Route>

Save the file and restart the service.

The first stanza, syslog\_tls, is just there for information. It's not actually used in this configuration. At a later date we'll be looking at encryption but there's a PKI to build.

This is all fairly self-explanatory. **OutputType Syslog\_TLS** is needed to enforce the RFC5424 standards along with **Exec to\_syslog\_ietf()**. Not sure why both are needed but they really are.

In the Eventlog config the QueryXML is extracted from Windows Event Log (**Event Viewer**  $\rightarrow$  **Custom View**  $\rightarrow$ . **Server Roles**. Right click on **Network Policy...**. Choose **Properties**, **Edit Filter**, **XML** and copy the XML into the NXLog config).

Some customisation might be needed to filter only for traffic between sites, rather than traffic to/from Jisc NRPS.

