RADSECProxy VLAN Assignment

```
### Used to add RADIUS attributes to drop all users onto VLAN 7
### The leading "'" is important as the number should be sent as a string
rewrite AddVLANAssignment {
    # Tunnel-Private-Group-Id = 7
    RemoveAttribute 81
    AddAttribute 81:'7

    # Tunnel-Type = VLAN
    RemoveAttribute 64
    AddAttribute 64:13

    # Tunnel-Medium-Type = IEEE-802
    RemoveAttribute 65
    AddAttribute 65:6

    # Filter-Id = 7
    RemoveAttribute 11
    AddAttribute 11:'7
}

server roaming0.govroam.uk {
           type = udp
           secret "secret"
           StatusServer minimal
           RewriteOut OutboundFilter
           RewriteIn AddVLANAssignment
}
server roaming1.govroam.uk {
           type = udp
           secret "secret"
           StatusServer minimal
           RewriteOut OutboundFilter
           RewriteIn AddVLANAssignment
}
server roaming2.govroam.uk {
           type = udp
           secret "secret"
           StatusServer minimal
           RewriteOut OutboundFilter
           RewriteIn AddVLANAssignment
}
server roaming3.govroam.uk {
           type = udp
           secret "secret"
           StatusServer minimal
           RewriteOut OutboundFilter
           RewriteIn AddVLANAssignment
```

```
}
```

From:
https://wiki.govroam.uk/dokuwiki/ - **Govroam**

Permanent link:
https://wiki.govroam.uk/dokuwiki/doku.php?id=siteadmin:radsecproxy_vlan_assignment&rev=1615301266

Last update: **2021/03/09 14:47**